

PRODUCT DATA SHEET

SMART BASIC



DESCRIPTION

In case of a water leakage, the central will signal the solenoid valve to stop the main water supply. The central will warn with an audio signal and display the location of the leakage.

APPLICATIONS

For use in homes, holiday homes and commercial buildings.

TECHNICAL SPECIFICATIONS

Mains voltage	230V AC 50hz
Alarm relay (NO-C-NC)	max. 24V DC 0,5A
Radio frequency system communication	868,3Mhz

MEASURES	HxWxD (mm)	Weight (g)
Central	134 x 199 x 32	643
3/4" valve	120 x 92 x 56	1135

Length power cable	1100mm
Length solenoid valve cable	1900mm

CONNECTIVITY

Unlimited number of wireless sensors
 2 ports for sensor cables
 Relay port for signal to domestic alarm etc.
 Ethernet for upgrading software

ADD-ONS

GSM modul for SMS alerts
 External antenna

PRODUCT VARIANTS

Complete with 1/2" valve	NRF no. 5648271
Complete with 3/4" valve	NRF no. 5648272
Central unit only	NRK no. 5648269

ASSOCIATED PRODUCTS

Solenoid valve 1/2"	NRF no. 5640101
Solenoid valve 1"	NRF no. 5640027
Split cable for two Solenoid valves	NRF no. 5648236
Central unit WTG 28-A	NRF no. 5648203
Adapter for wireless solenoid valve control	NRF no. 5648222

PACKAGE CONTENTS

