



7-CHANNELS

DESCRIPTION

In case of leakage the control unit will signal the solenoid valve to close the main water supply. The control unit will emit a warning signal, and indicate where the leakage is located.

APPLICATIONS

The 7-channels is intended for use in commercial buildings and apartment buildings.

TECHNICAL SPECIFICATIONS

Mains voltage	230V AC 50 Hz
Power consumption (no alarm)	13,3 mA
Power consumption (upon alarm, incl. valve)	101,5 mA

MEASURES	$H \times W \times D \text{ (mm)}$	Weight (g)
Control unit	80 (112) × 160 × 64	740
Valve 3/4"	120 x 92 x 56	1135

CABLES

Length solenoid valve cable	1350 mm
Length power cable	1050 mm

CONNECTIVITY

7 ports for sensor cables Leakage alarm ports: C-NC-NO

PRODUCT VARIANTS

Complete with 1/2" valve	NRF no. 5648216
Complete with 3/4" valve	NRF no. 5648217
Control unit only	NRF no. 5648205

ASSOCIATED PRODUCTS

Solenoid valve 1/"2	NRF no. 5640101
Solenoid valve 3/4"	NRF no. 5640201
Solenoid valve 1"	NRF no. 5640027
Split cable for 2 valves	NRF no. 5648236

PACKAGE CONTENTS









WATERGUARD

Nedre Storgate 46 post@waterguard.no

